

EnerGalactic-2280

EnerGalactic-2280-1C

COSPOWERS



Temperature Difference
inside the Battery
Pack: <5°C



High Safety
3 Level Fire
Protection



High Energy Density
for Flexible Layout
and Expansion



Modular Prefabrication
No On-site Installation
Required

Parameters/ Model		EnerGalactic-2280	EnerGalactic-2280-1C
Battery Module	Cell Capacity	100Ah	
	Battery Pack	3P18S	
	Module Voltage	57.6V	
	Module Power	17.280kWh	
	Size	295*880*361mm	
Battery Cluster	NOs.of Modules	22pcs	
	Cluster Nominal Voltage	1267.2V	
	Voltage Range	1108.8V~1405.8V	
	Single Cluster Power	380.16kWh	
	Battery Rack Dimension	1400*855*2360mm	
Battery Cabin	Nos. of Battery Clusters	6pcs	
	Battery system energy	2.28MWh	
	Battery Cabin Dimension	20 feet	
	Cooling Method	Air cooling	
	IP Class	IP54	



Cospowers Technology Co., Ltd.

W: WWW.COSPOWERS.COM

A: No.28, Dongqi Road, Dongying City, Shandong Province, P.R.C.

T: +86-546-7768891

Copyright and final interpretation rights belong to Cospowers Technology Co., Ltd.