

EnerGalactic-3000

EnerGalactic-1650

COSPOWERS



Temperature Difference
inside the Battery
Pack: <math><5^{\circ}\text{C}</math>



High Safety
3 Level Fire
Protection



High Energy Density
for Flexible Layout
and Expansion



Modular Prefabrication
No On-site Installation
Required

Parameters/ Model		EnerGalactic-3000	EnerGalactic-1650
Battery Module	Cell Capacity	100Ah	60Ah
	Battery Pack	3P14S	2P20S
	Module Voltage	44.8V	64V
	Module Power	13.440kWh	7.680kWh
	Size	295*689*361mm	290*685*277mm
Battery Cluster	NOs.of Modules	16pcs	12pcs
	Cluster Nominal Voltage	716.8V	768.0V
	Voltage Range	627.2~795.2V	672.0~852.0V
	Single Cluster Power	215.040kWh	92.160kWh
	Battery Rack Dimension	1200*702*2350mm	900*671*2230mm
Battery Cabin	Nos. of Battery Clusters	14pcs	18pcs
	Battery system energy	3.011MWh	1.659MWh
	Battery Cabin Dimension	40 feet	40 feet
	Cooling Method	Liquid cooling	Liquid cooling
	IP Class	IP54	IP54



Cospowers Technology Co., Ltd.

W: WWW.COSPOWERS.COM

A: No.28, Dongqi Road, Dongying City, Shandong Province, P.R.C.

T: +86-546-7768891

Copyright and final interpretation rights belong to Cospowers Technology Co., Ltd.