

5-15 mins 6C series



- 1 Higher safety and stability lithium iron phosphate battery, no fire caused by thermal runaway
- 2 Pre installed battery system, modular standard design, rapid deployment on site, easy operation and maintenance
- 3 Longcycle life, 4000 times @0.5C/0.5C@80%DOD@25°C
- 4 SupportingHVDC, UPS system, and compatible with UPS system N line
- 5 Touch LCD to display various parameters, records and status visually
- 6 Support multiple groups in parallel, and support uninterrupted power maintenance when multiple clusters are used in parallel
- 7 Three-level BMS management, multi-level protection, automatic isolation in the event of anomalies, to ensure normal power supply to the system
- 8 High energy density, saving 70%compared to lead-acid battery
- 9 Optional non-electric self-starting cabinet-level fire protection system, accurate and rapid fire extinguishing
- 10 Natural heat dissipation design, saving energy

Product parameters

Product model	CF48050U	CF51250U	CF24050U
Cell material	LFP	LFP	LFP
Nominal voltage	480Vdc	512Vdc	240Vdc
Standard charge current	525Vdc	560Vdc	262.5Vdc
Standard capacity	50Ah/24kWh	50Ah/25.6kWh	50Ah/12kWh
Self-discharge rate	≤3% (0~30°C/3months)	≤3% (0~30°C/3 months)	≤3% (0~30°C/3 months)
Standard discharge current	50Acontinuous discharge (1C)	50Acontinuous discharge (1C)	50Acontinuous discharge (1C)
Max discharge current	300Acontinuous discharge (6C)	300Acontinuous discharge (6C)	300Acontinuous discharge (6C)
Standard charge current	25A (0.5C)	25A (0.5C)	25A (0.5C)
Max charge current	50A (1C)	50A (1C)	50A (1C)
Cell			
Nominal capacity	50Ah	50Ah	50Ah
Nominal voltage	3.2Vdc	3.2Vdc	3.2Vdc
Operating voltage range	2.5~3.6Vdc	2.5~3.6Vdc	2.5~3.6Vdc
Weight	1.455Kg	1.455Kg	1.455Kg
Battery module			
Configuration	1P15S	1P16S	1P15S
Nominal capacity	50Ah	50Ah	50Ah
Nominal voltage	48Vdc	48Vdc	48Vdc
Operating voltage range	42~52.5Vdc	42~52.5Vdc	42~52.5Vdc
Weight	31Kg	31Kg	31Kg
Cluster			
Configuration	1P150S	1P160S	1P75S
Nominal capacity	50Ah	50Ah	50Ah
Nominal voltage	480Vdc	512Vdc	240Vdc
Operating voltage range	420~525Vdc	448~560Vdc	210~262.5Vdc
Weight	430Kg	450Kg	210Kg



Harbin Coslight New Energy co., Ltd.

W: WWW.COSPOWERS.COM

A: No.8,Taihunan Road, Yingbin Road Concentration Zone, Development Zone, Harbin City,Heilongjiang Province,P.R.C

T: +86-451-51016603

Copyright and final interpretation rights belong to Harbin Coslight New Energy Co., Ltd.