

# EnerGalactic-3350

# EnerGalactic-3760

**COSPOWERS**



Temperature Difference  
inside the Battery  
Pack: <3°C



High Safety Fire  
Protection at the  
Pack Level



High Energy Density  
for Flexible Layout  
and Expansion



Modular Prefabrication  
No On-site Installation  
Required

	Parameters/ Model	EnerGalactic-3350	EnerGalactic-3760
Battery Module	Cell Capacity	280Ah	314Ah
	Battery Pack	1P52S	1P52S
	Module Voltage	166.4V	166.4V
	Module Power	46.592kWh	52.2496kWh
	Size	855*1157*252mm	855*1087*252mm
	IP Class	IP67	IP67
Battery Cluster	NOs.of Modules	8pcs	8pcs
	Cluster Nominal Voltage	1331.2V	1331.2V
	Voltage Range	1164.8~1476.8V	1164.8~1476.8V
	Single Cluster Power	372.736kWh	417.997kWh
	Battery Rack Dimension	972*1157*2480mm	972*1157*2480mm
Battery Cabin	Nos. of Battery Clusters	9pcs	9pcs
	Battery system energy	3.355MWh	3.762MWh
	Battery Cabin Dimension	20 feet	20 feet
	Cooling Method	Liquid cooling	Liquid cooling
	IP Class	IP54	IP54



Cospowers Technology Co., Ltd.

W: WWW.COSPOWERS.COM

A: No.28, Dongqi Road, Dongying City, Shandong Province, P.R.C.

T: +86-546-7768891

Copyright and final interpretation rights belong to Dongying Cospowers Technology Co., Ltd.