

EnerGalactic-6700

COSPOWERS



Product capacity is increased by 15%+



Through-go large Pack design



System cycle energy efficiency is increased by 1%+



Support one-line /back-to-back arrangement, saving 35% of land area

Parameters/ Model		EnerGalactic-6700
DC side basic parameters	Cell Capacity	720Ah
	Battery pack	1P52S
	Module quantity in single cluster	8pcs
	Nos. of Battery Clusters	7pcs
	Battery system power	6.709MWh
	Rated AC power	1331.2V DC
	Voltage Range	1164.8-1476.8V DC
	Rated charge and discharge power	3354kW
System level parameters	Operating temperature	-30~55°C
	Ambient Humidity	0~95% (no condensation)
	Working Altitude	2000m
	Communication method	Ethernet, RS485, CAN
	Protection level	IP54
	Anti-salt spray level	C4(C5 optional)
	Cooling Method	Liquid cooling
	Noise	≤65dB
	Fire protection system	Cabin level sevofluoropropane/perfluorohexanoneor/aerosol + water fire protection + flammable gas detection + explosion-proof ventilation system
	Size (W*D*H)	2438*6058*2896mm
	Weight	55t
	Meets standards	GB/T 36276, GB/T 34131 UN3536, IEC63056, UL9540



Cospowers Technology Co., Ltd.
W: WWW.COSPOWERS.COM
A: No.28, Dongqi Road, Dongying City, Shandong Province, P.R.C.
T: +86-546-7768891
Copyright and final interpretation rights belong to Cospowers Technology Co., Ltd.